



Highly Flexible Metal Protection Conduit; Robust; Hooked Metal Profile



Properties

IP40 to EN/IEC 60529

Highly flexible

Extremely heat resistant

Increased resistance to tear, pressure and impact

Conforms to RoHS guideline

Temperature range

400° C

Delivery variants

Further diameters and lengths available on request

Design material

Profiled metal strip, galvanised steel; hooked profile

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Highly Flexible Metal Protection Conduit; Robust; Hooked Metal Profile

Nominal width connecting part	I.D. mm	O.D. mm	Bending Radius (middle of hose)	Weight kg/m	PU
- *	5	7	20	0,05	50
- *	6	8	21	0,05	50
- *	7	9	23	0,06	50
10	8	10	25	0,07	10
10	8	10	25	0,07	50
- *	10	13	32	0,11	50
14	11	14	34	0,12	10
14	11	14	34	0,12	50
- *	13	16	40	0,14	50
17	14	17	40	0,15	10
17	14	17	40	0,15	50
- *	15	18	45	0,16	50
19	16	19	45	0,17	10
19	16	19	45	0,17	50
- *	17	20	50	0,18	50
21	18	21	50	0,19	10
21	18	21	50	0,19	50
- *	22	26	65	0,31	50
27	23	27	67	0,32	10
27	23	27	67	0,32	50
- *	29	34	85	0,42	25
36	31	36	90	0,45	10
36	31	36	90	0,45	25
- *	38	43	105	0,54	25
45	40	45	110	0,56	10
45	40	45	110	0,56	25
- *	45	50	120	0,63	25
52	47	52	125	0,66	10
52	47	52	125	0,66	25
- *	49	54	130	0,68	25
56	51	56	140	0,71	10
56	51	56	140	0,71	25

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com