



Non-Rusting And Highly Flexible Stainless Steel Protection Conduit; Robust; Hooked Metal Profile



Properties

IP 40 to EN/IEC 60529

Extremely heat resistant

Increased resistance to tear, pressure and impact

Conforms to RoHS guideline

Highly flexible

Temperature range

600 °C

Delivery variants

Further diameters and lengths available on request

Design material

Profiled metal strip, stainless steel (INOX); hooked profile

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com

Non-Rusting And Highly Flexible Stainless Steel Protection Conduit; Robust; Hooked Metal Profile

Nominal width connecting part	I.D. mm	O.D. mm	Bending Radius (middle of hose)	Weight kg/m	PU
5	3	5	15	0,04	50
6	4	6	15	0,05	50
7	5	7	17	0,05	50
8	6	8	20	0,06	50
10	8	10	25	0,07	50
14	11	14	34	0,12	50
17	14	17	40	0,15	50
19	16	19	45	0,17	50
21	18	21	50	0,19	50
27	23	27	67	0,32	50
36	31	36	90	0,50	25
45	40	45	110	0,70	25

Get in contact with our team in The Netherlands or Belgium

The Netherlands

Freddy van Riemsdijkweg 7
5657 EE Eindhoven

+31 (0)40 20 88 088
sales@avt-connecting.com
www.avt-connecting.com

Belgium

Grauwmeer 1/45 Bus 43
B-3001 Heverlee

+32 (0)16 400 500
sales@avt-connecting.be
www.avt-connecting.com